# SAFETY DATA SHEET



## Texwipe® Pre-sat wipers w/MPK

# **Section 1. Identification**

**GHS** product identifier : Texwipe® Pre-sat wipers w/MPK

: TX9625, TX8348, TX8352 **Product code** 

: Pre-wetted wipers. **Product type** 

#### **Identified uses**

For use in various cleaning applications.

Supplier/Manufacturer : Texwipe

> 1210 South Park Drive Kernersville, NC 27284

Tel: 1-(336) 996-7046 (Toll Free: 1-(800) 839-9473)

Fax: 1-(336) 996-6563 Web: www.texwipe.com

**Emergency telephone** number (with hours of

operation)

: CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3887

# Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE SOLIDS - Category 2 ACUTE TOXICITY (oral) - Category 4

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

CARCINOGENICITY - Category 2

**GHS label elements** 

**Hazard pictograms** 







Signal word : Warning

: H228 - Flammable solid. **Hazard statements** 

H302 - Harmful if swallowed.

H319 - Causes serious eye irritation. H351 - Suspected of causing cancer.

**Precautionary statements** 

**Prevention** : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves. Wear eye or face protection: Recommended: Safety

glasses. Wear protective clothing.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash hands thoroughly after handling.



## Section 2. Hazards identification

Response : P308 + P313 - IF exposed or concerned: Get medical attention.

P301 + P312 + P330 - IF SWALLOWED: Call a POISON CENTER or physician if you

feel unwell. Rinse mouth.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

Storage: P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazards not otherwise

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture

Other means of identification

: Mixture

: Not available.

Ingredient name	%	CAS number
	80 - 100 5 - 10	107-87-9 108-10-1

Final product is comprised of solid cloth media that is saturated with the above components. Fill volume is controlled to ensure that no free liquid is present in the final product packaging.

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

### **Description of necessary first aid measures**

Eye contact : I

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

: Flush contaminated skin with plenty of water. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention



# Section 4. First aid measures

immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.Skin contact : No known significant effects or critical hazards.

Ingestion : Harmful if swallowed.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet or water-based fire extinguishers.

Specific hazards arising from the chemical

: Flammable solid.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide

carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.



# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.



# Section 8. Exposure controls/personal protection

## **Control parameters**

## **United States**

## Occupational exposure limits

Ingredient name	<b>Exposure limits</b>	
Pentan-2-one	NIOSH REL (United States, 10/2016). TWA: 150 ppm 10 hours.	
	TWA: 130 ppin 10 hours.	
	OSHA PEL (United States, 6/2016).	
	TWA: 200 ppm 8 hours.	
	TWA: 700 mg/m³ 8 hours.	
	ACGIH TLV (United States, 3/2017).	
	STEL: 150 ppm 15 minutes.	
4-Methylpentan-2-one	ACGIH TLV (United States, 3/2017).	
	TWA: 20 ppm 8 hours.	
	STEL: 75 ppm 15 minutes.	
	NIOSH REL (United States, 10/2016).	
	TWA: 205 mg/m³ 10 hours. STEL: 75 ppm 15 minutes.	
	STEL: 300 mg/m³ 15 minutes.	
	TWA: 50 ppm 10 hours.	
	OSHA PEL (United States, 6/2016).	
	TWA: 100 ppm 8 hours.	
	TWA: 410 mg/m³ 8 hours.	

## **Canada**

#### Occupational exposure limits

Ingredient name	Exposure limits
Pentan-2-one	CA Alberta Provincial (Canada, 4/2009).  8 hrs OEL: 200 ppm 8 hours.  15 min OEL: 250 ppm 15 minutes.  8 hrs OEL: 705 mg/m³ 8 hours.  15 min OEL: 881 mg/m³ 15 minutes.  CA British Columbia Provincial (Canada, 7/2016).  TWA: 150 ppm 8 hours.  STEL: 250 ppm 15 minutes.  CA Ontario Provincial (Canada, 7/2015).  STEL: 150 ppm 15 minutes.  CA Quebec Provincial (Canada, 1/2014).  TWAEV: 530 mg/m³ 8 hours.  TWAEV: 530 mg/m³ 8 hours.  CA Saskatchewan Provincial (Canada, 7/2013).  STEL: 250 ppm 15 minutes.  TWA: 200 ppm 8 hours.
4-Methylpentan-2-one	CA Alberta Provincial (Canada, 4/2009).  8 hrs OEL: 205 mg/m³ 8 hours.  8 hrs OEL: 50 ppm 8 hours.  15 min OEL: 75 ppm 15 minutes.  15 min OEL: 307 mg/m³ 15 minutes.  CA British Columbia Provincial (Canada, 7/2016).  TWA: 20 ppm 8 hours.  STEL: 75 ppm 15 minutes.  CA Ontario Provincial (Canada, 7/2015).  TWA: 20 ppm 8 hours.  STEL: 75 ppm 15 minutes.  CA Quebec Provincial (Canada, 1/2014).  TWAEV: 50 ppm 8 hours.  TWAEV: 205 mg/m³ 8 hours.  STEV: 307 mg/m³ 15 minutes.  CA Saskatchewan Provincial (Canada, 7/2013).  STEL: 75 ppm 15 minutes.  TWA: 50 ppm 8 hours.



# Section 8. Exposure controls/personal protection

# Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

#### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: Safety glasses.

## **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

## **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

### <u>Appearance</u>

Physical state : Solid.
Color : Colorless.
Odor : Ketone.
Odor threshold : Not available.
pH : Not available.

Melting point: Not available.Boiling point: Not available.

Flash point : Closed cup: 7.8°C (46°F) [Pensky-Martens.]

**Evaporation rate** : Not available.





# Section 9. Physical and chemical properties

Flammability (solid, gas)

Lower and upper explosive

(flammable) limits

Not available.Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.

Solubility
Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).

**Incompatible materials**: Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

### Information on toxicological effects

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Pentan-2-one	LD50 Dermal	Rabbit	6500 mg/kg	-
	LD50 Oral	Rat	1600 mg/kg	-
4-Methylpentan-2-one	LD50 Oral	Rat	2080 mg/kg	-

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Pentan-2-one	Skin - Mild irritant	Rabbit	-	405 mg	-
4-Methylpentan-2-one	Eyes - Moderate irritant	Rabbit	-	24 hours 100 μl	-
	Eyes - Severe irritant	Rabbit	-	40 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-

#### **Sensitization**

There is no data available.

#### **Mutagenicity**

There is no data available.

#### **Carcinogenicity**





# **Section 11. Toxicological information**

### Classification

Product/ingredient name	OSHA	IARC	NTP
4-Methylpentan-2-one	-	2B	-

#### Reproductive toxicity

There is no data available.

#### **Teratogenicity**

There is no data available.

### Specific target organ toxicity (single exposure)

Name	Category	Target organs
4-Methylpentan-2-one	Category 3	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

There is no data available.

### **Aspiration hazard**

There is no data available.

Information on the likely

routes of exposure

Dermal contact. Eye contact. Inhalation. Ingestion.

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.

**Ingestion** : Harmful if swallowed.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

## Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : No known significant effects or critical hazards.

effects

effects

Potential delayed effects : No known significant effects or critical hazards.

**Long term exposure** 

**Potential immediate** : No known significant effects or critical hazards.

\_ . . . . . . .

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.





# **Section 11. Toxicological information**

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

### **Numerical measures of toxicity**

## **Acute toxicity estimates**

Route	ATE value
Oral Inhalation (vapors)	1620.6 mg/kg 200 mg/L

# **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
4-Methylpentan-2-one	Acute LC50 505000 µg/L Fresh water Chronic NOEC 78 mg/L Fresh water		96 hours 96 hours 21 days 33 days

### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Pentan-2-one	0.91	-	low
4-Methylpentan-2-one	1.9		low

### **Mobility in soil**

Soil/water partition coefficient (Koc)

Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### United States - RCRA Toxic hazardous waste "U" List





# Section 13. Disposal considerations

Ingredient	CAS#		Reference number
4-Methylpentan-2-one	108-10-1	Listed	U161

# **Section 14. Transport information**

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN3175	UN3175	UN3175	UN3175
UN proper shipping name	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Pentan-2-one, 4-Methylpentan-2-one)			
Transport hazard class(es)	4.1	4.1	4.1	4.1
Packing group	III	III	III	III
Environmental hazards	No.	No.	No.	No.

**AERG** : 133

**Additional information** 

DOT Classification : Remarks

Limited quantity

**TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.20-2.22 (Class 4).

**Remarks** Limited quantity

IMDG : Remarks Limited quantity

IATA : Remarks

Limited quantity

**Special precautions for user**: **Transport within user's premises**: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

# **Section 15. Regulatory information**

U.S. Federal regulations

: United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112

: Listed

(b) Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602

: Not listed

Class I Substances

Clean Air Act Section 602 : No

: Not listed

Class II Substances

**DEA List I Chemicals** (Precursor Chemicals)

: Not listed



# Section 15. Regulatory information

**DEA List II Chemicals** (Essential Chemicals)

: Listed

#### **SARA 302/304**

#### **Composition/information on ingredients**

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : FLAMMABLE SOLIDS - Category 2

ACUTE TOXICITY (oral) - Category 4

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

CARCINOGENICITY - Category 2

#### Composition/information on ingredients

Name	Classification
	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
4-Methylpentan-2-one	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

### **SARA 313**

	Product name	CAS number
Form R - Reporting requirements	4-Methylpentan-2-one	108-10-1
Supplier notification	4-Methylpentan-2-one	108-10-1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### State regulations

Massachusetts : The following components are listed: Pentan-2-one; 4-Methylpentan-2-one

New York : The following components are listed: 4-Methylpentan-2-one

New Jersey : The following components are listed: Pentan-2-one; 4-Methylpentan-2-one Pennsylvania : The following components are listed: Pentan-2-one; 4-Methylpentan-2-one

#### California Prop. 65

**WARNING**: This product can expose you to 4-Methylpentan-2-one, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### **Canada**

#### **Canadian lists**

Canadian NPRI : The following components are listed: 4-Methylpentan-2-one

CEPA Toxic substances : None of the components are listed.

Canada inventory (DSL : All components are listed or exempted.

NDSL)



# **Section 16. Other information**

## Procedure used to derive the classification

Classification	Justification
FLAMMABLE SOLIDS - Category 2	Expert judgment
ACUTE TOXICITY (oral) - Category 4	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 2	Calculation method

### **History**

Date of issue mm/dd/yyyy : 09/15/2018

Date of previous issue : Not applicable

Version : 1

Prepared by : KMK Regulatory Services Inc.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

